

Reflective tape

T-1500



Standard dimensions reflective tape T1500			
itemno.:	dimension	colour	
14446110	15mmx45,70m	white	
14446130	15mmx45,70m	red	
13196120	20mmx45,70m	amber	
15106110	25mmx45,70m	white	
06806110	50mmx45,70m	white	
06806130	50mmx45,70m	red	
11006122	70mmx45,70m	amber	
11006123	100mmx45,70m	amber	
11006124	200mmx45,70m	amber	
07506110	250mmx45,70m	white	
07506130	250mmx45,70m	red	
07506111	610mmx45,70m	white	

REFLEKTOR DATEN

Application	Reflective tape
Item	T-1500
Item no.	07506111

TECHNICAL SPECIFICATIONS

Shape	roll
Size (LxWxH)	45700x610x0,1 mm
Reflective size (LxW)	45700x610 mm
Tolerance	TG5 [DIN 16742]
Mounting	to be glued (with tape)
Chemical resistance	Standard
Protection	IP67
Operating temp.	-20°C to +65°C
Surface	Standard
Optical structure	Glass balls
Optic size	0
Polarizing rotation	no
Application	photoelectric sensors without polarizing filter

MATERIAL DATA

|--|

DESCRIPTION

For simple applications with photoelectric sensors or for use on warning signs, traffic signs and markings, the T-1500 reflective tape on a glass ball basis is suitable. The tape is not suitable for use with photoelectric sensors with polarizing filters. The reflective tape is UV-resistant, has a self-adhesive backing and is suitable for outdoor applications. There are many colors available. The film can be punched and cut and is available in rolls of 45.7 m in length and up to a width of 1220 mm.